	东莞市九木精密电子有限公司 Dongguan Joint more precision electronics Co.,Ltd.	LANGUAGE
		CHINESE ENGLISH

【1. 適用範圍 SCOPE】

此種規格包括 SATA 1.27mm Pitch 刺破式連接器系列須
This specification Covers the SATA 1.27mm Pitch IDC Pothook Connector Series.

【2. 規格與料號 Spec and Part number】

規格內容 / Specification	產品料號 / Production No.
端子/Terminal	A3801-XXX
膠殼/Housing	A3801H-05P
蓋子/Cover	A3801WV/WR-XXX

【3. 材質與表面處理 Disposal of Material and surface】

規格內容 / Specification	材質 / Materials	表面處理 / Disposal of Surface
端子/Terminal	磷銅/Phosphor Bronze	Nickel: 20 μ" Gold Flash: 1 μ" or 3 μ" and 15 μ"
膠殼/Housing	PBT/PBT+ GF 15%	UL 94V-0
蓋子/Cover	PA 66 or PBT+15%GF	UL 94V-0


(上述参数请以工程图为准/Please Refer to the Project drawing for the above Specification)

【4. 額定等級 Ratings and applicable wires】

項目【Item】	規格【Standard】	
額定電壓 Rated Voltage (Max.)	15V	[AC/DC]
額定電流 Rated Current (Max.)	1.5A	
使用溫度範圍 Ambient temperature Range	-40°C ~ +105°C	
適用線徑 Applicable wire insulation O.D	AWG18#、20#、22# Insulation O.D. 2.10mm(Max.)	

*升溫時含端子. Including terminal temperature rise.

A/1	NEW	TITLE: SATA 1.27mm Pitch IDC Pothook Series			Sheet: 1 of 6
REV.	DESCRIPTION	WRITTEN BY:	CHECKED BY: K B. Sun	APPROVED BY: Succeed. Sun	DATE: YR/MO/DAY 2017/06/03


	东莞市九木精密电子有限公司 Dongguan Joint more precision electronics Co.,Ltd.	LANGUAGE
		CHINESE ENGLISH

【5. 性能 PERFORMANCE】

5-1. 電氣的性能 Electrical Performance.

項 目 【Item】		條 件 【Test Condition】	規 格 【Requirement】
5-1-1	接觸阻抗 Contact Resistance	公母配合, 開放電壓 20mV 以下, 電流 10mA 檢測連接器. Mate connectors, measure by dry circuit, 20mV MAX, 10mA. (Based upon EIA-364-06A).	20 milliohms Max.
5-1-2	絕緣阻抗 Insulation Resistance	公母配合, 在相鄰端子, 端子與地片之間, 使用 500V 的直流電, 檢測連接器. Mate connectors, apply 500V DC between adjacent terminal or ground. (Based upon EIA-364-21B / MIL-STD-202 Method 302 Cond. B)	1000 Megohms Min.
5-1-3	耐電壓 Dielectric Strength	公母配合, 在相鄰端子, 端子與地片之間, 使用 500V 的交流電 1 分鐘, 檢測連接器. Mate connectors, apply 500V AC for 1 minute between adjacent terminal or ground. (Based upon EIA-364-20A / MIL-STD-202 Method 301)	不出現中斷等情況 No Breakdown and Flashover
5-1-4	壓線後端子接觸阻抗 Contact resistance on crimped portion	鉚線後之端子, 開放電壓 20mV 以下, 電流 10mA 檢測連接器. Crimp the applicable wire on to the terminal measure by dry circuit 20mV MAX, 10mA.	10 milliohms Max.


A/1	NEW	TITLE: SATA 1.27mm Pitch IDC Pothook Series			Sheet: 2 of 6
REV.	DESCRIPTION	WRITTEN BY:	CHECKED BY: K B. Sun	APPROVED BY: Succeed. Sun	DATE: YR/MO/DAY 2017/06/03

	东莞市九木精密电子有限公司 Dongguan Joint more precision electronics Co.,Ltd.	LANGUAGE
		CHINESE ENGLISH

5-2. 機械的性能 Mechanical Performance.

項 目 【Item】		條 件 【Test Condition】	規 格 【Requirement】		
5-2-1	插拔力 Insertion and Withdrawal Force	以每分鐘 25±3mm 的速率插入和拔出. Insert and withdraw connectors at the speed rate of 25 ± 3mm/minute.	參照第 6 項 Refer to paragraph 6		
5-2-2	端子保持力 Terminal/ Housing Retention Force	以每分 25±3mm 的速率, 將端子從 Housing 內軸向拔出的力量. Apply axial pull out force at the speed rate of 25±3mm/minute on the terminal assembled in the housing.	19.6N {2kgf} Min.		
5-2-3	端子壓著強度 Tensile strength (Crimped connections)	固定壓線後的端子, 使電線與端子分離時所需的最小力量. Fix the crimped terminal, apply axial pull out force on the wire. (Do not crimp insulation part).	Spec. kgf Min.		
			線型 AWG	水準方向拉力 Level Pull	垂直方向拉力 Plumb Pull
			AWG#18	2.00Kgf/Min	1.00 Kgf/Min
			AWG#20	1.80 Kgf/Min	0.90 Kgf/Min
			AWG#22	1.60 Kgf/Min	0.80 Kgf/Min
			Note> As for unspecified wire sizes in this specification define values with clients		

A/1	NEW	TITLE: SATA 1.27mm Pitch IDC Pothook Series			Sheet: 3 of 6
REV.	DESCRIPTION	WRITTEN BY:	CHECKED BY: K B. Sun	APPROVED BY: Succeed. Sun	DATE: YR/MO/DAY 2017/06/03

	东莞市九木精密电子有限公司 Dongguan Joint more precision electronics Co.,Ltd.	LANGUAGE
		CHINESE ENGLISH

5-3. 環境性能及其它 Environmental Performance and Others.

項目 【Item】		條件 【Test Condition】	規格 【Requirement】	
5-3-1	重復插拔 Repeated Insertion/ Withdrawal	以每分鐘不超過 10 次的速率, 將公母插拔 50 次. When mated up to 50 cycles repeatedly by the rate of 10 cycles per minute.	接觸阻抗 Contact Resistance	40 milliohms Max.
5-3-2	溫升測試 Temperature Rise	公母對插後, 在通過額定電流下, 所測定的溫度. Carrying rated current load. (UL 1997)	溫升測試 Temperature rise	30°C Max.
5-3-3	耐振動性 Vibration	振幅: 1.5mm P-P 時間: 10~55~10 HZ in 1 minute 持續時間: 每軸向 2 小時 Amplitude: 1.5mm P-P Sweep time: 10~55~10 HZ in 1 minute Duration: 2 hours in each X. Y. Z axial. (Based upon EIA-364-28B/MIL-STD-202 Method 213B Cond. A)	外觀 Appearance	無異狀 No Damage
			接觸阻抗 Contact Resistance	40 milliohms Max.
			瞬斷 Discontinuity	1 micro-second Max.
5-3-4	耐衝擊性 Shock	在 X. Y. Z 上 6 個方向上, 以 490m/s ² (50g 的力量)各擊下. 490m/s ² {50G}, 3 strokes in each X. Y. Z. axes. (Based upon EIA-364-27B/MIL-STD-202 Method 213B Cond. A)	外觀 Appearance	無異狀 No Damage
			接觸阻抗 Contact Resistance	40 milliohms Max.
			瞬斷 Discontinuity	1 micro-second Max.
5-3-5	耐熱性 Heat Resistance	85±2°C, 96 hours. (Based upon MIL-STD-202 Method 108A Cond. A)	外觀 Appearance	無異狀 No Damage
			接觸阻抗 Contact Resistance	40 milliohms Max.

A/1	NEW	TITLE:			Sheet: 4 of 6
		SATA 1.27mm Pitch IDC Pothook Series			
REV.	DESCRIPTION	WRITTEN BY:	CHECKED BY:	APPROVED BY:	DATE: YR/MO/DAY
			K B. Sun	Succeed. Sun	2017/06/03



項 目 【Item】		條 件 【Test Condition】	規 格 【Requirement】	
5-3-6	耐寒性 Cold Resistance	-25 ± 5 °C , 96 hours. (Based upon EIA-364-105)	外觀 Appearance	無異狀 No Damage
			接觸阻抗 Contact Resistance	40 milliohms Max.
5-3-7	耐濕性 Humidity	溫度: 40±2°C 濕度: 90~95%(RH) 持續時間: 96 hours Temperature: 40±2°C Relative Humidity: 90~95% Duration: 96 hours (Based upon EIA-364-31A/MIL-STD-202 Method 103B Cond. B)	外觀 Appearance	無異狀 No Damage
			接觸阻抗 Contact Resistance	40 milliohms Max.
			耐電壓 Dielectric Strength	Must meet 5-1-3
			絕緣阻抗 Insulation Resistance	100 Megohms MIN
5-3-8	溫度變化 Temperature Cycling	從-55°C持續 30 分鐘升至+85°C持續 30 分鐘, 循環 5 次. 5 cycles of: a) -55°C 30 minutes. b) +85°C 30 minutes. (Based upon EIA-364-32B)	外觀 Appearance	無異狀 No Damage
			接觸阻抗 Contact Resistance	40 milliohms Max.
5-3-9	鹽水噴霧 Salt Spray	在溫度 35±2°C, 鹽水濃度 5±1%下, 鹽水噴霧 8±1 小時. 8±1 hours exposure to a salt spray from the 5 ± 1% solution at 35 ± 2 °C . (Based upon EIA-364-26A/MIL-STD-202 Method 101D Cond. B).	外觀 Appearance	無異狀 No Damage
			接觸阻抗 Contact Resistance	40 milliohms Max.

A/1	NEW	TITLE: SATA 1.27mm Pitch IDC Pothook Series			Sheet: 5 of 6
REV.	DESCRIPTION	WRITTEN BY:	CHECKED BY: K B. Sun	APPROVED BY: Succeed. Sun	DATE: YR/MO/DAY 2017/06/03



項 目 【Item】		條 件 【Test Condition】	規 格 【Requirement】	
5-3-10	焊錫附著性 Solder-ability	焊接時間: 3±0.5 秒. 焊接溫度: 250±5°C. Soldering Time: 3±0.5second. Solder Temperature: 250±5°C. (Based upon EIA-364-52)	Solder Wetting	浸漬面積需 95%以上 95% of immersed area must show no voids, pin holes.
5-3-11	焊錫耐熱性 Solder-Resistance	焊接時間: 5±1 秒. 焊接溫度: 260±5°C. Soldering time:5±1sec solder. Temperature:260±5°C. (Based upon EIA-364-56A)	外觀 Appearance	無異狀 No Damage


(): 參考規格: Reference Standard { }: 參考單位: Reference

Unit

【6. 綜合插入力及拔出力 INSERTION/WITHDRAWAL FORCE】 <Connector mating force>

插入力(Max.)	拔出力(Min.)
4.50	1.00

A/1	NEW	TITLE: SATA 1.27mm Pitch IDC Pothook Series			Sheet: 6 of 6
REV.	DESCRIPTION	WRITTEN BY:	CHECKED BY: K B. Sun	APPROVED BY: Succeed. Sun	DATE: YR/MO/DAY 2017/06/03

	东莞市九木精密电子有限公司 Dongguan Joint more precision electronics Co.,Ltd.	LANGUAGE
		CHINESE ENGLISH

A/1	NEW	TITLE: SATA 1.27mm Pitch IDC Pothook Series			Sheet: 7 of 6
REV.	DESCRIPTION	WRITTEN BY:	CHECKED BY: K B. Sun	APPROVED BY: Succeed. Sun	DATE: YR/MO/DAY 2017/06/03